


3-PORT SCREWED FEMALE BALL VALVES PN 6 (–15...+120 °C)

XDG 3..



APPLICATION

Designed for zoned, solar, DHW production, chilled water, etc plants.

Features

- Chromed brass body and ball; Teflon and Viton seals.
- Fluid temperature: +5 ... +120 °C (with CRB ..., CVC ... & CVH ...); down to –15 °C (with CVC .../T & CVH .../T).
- Connections: tapered female as per UNI EN 10226-1:2006

Code	DN	Kvs(1) m³/h	Suitable actuator			Data Sheet
			CRB - CVC	CVC ... bar(2)	CVH 63./21./05.	
	SREWED		bar (²)	bar (²)	bar (²)	
XDG 315	1/2"	3,9	6	6	6	M 918
XDG 320	3/4"	7,9	6	6	6	M 918
XDG 325	1"	13	6	6	6	M 918
XDG 332	1"1/4	20,7	6	6	6	M 918
XDG 340	1"1/2	38,7	–	6	6	M 918
XDG 350	2"	54	–	6	–	M 918

(1) : Kvs - Flow coefficient: Flow in m³/h with valve open and pressure drop of 100 kPa.
100 kPa = 10 mWG = 1 bar

(2) : bar - Maximum pressure differential (?p max) permitted by actuator.